

Model MF 314

W.H.O. Approved PQS Code E003/023

MF 314 is a combined vaccine and icepack freezer. The thermostat ensures stable temperature control in the range from -18°C to -28°C. Temperature can be monitored on the external digital display. Holdover time in case of power cut is improved with the unit's thick 100mm insulation. The corrosion proof steel cabinet protects against rust, while the evaporator tubing is zinc coated.



Features

- Extra compartment for icepack freezing
- External cabinet pre-painted galvanized steel
- Internal liner pre-painted galvanized steel
- Available in 220V-240V 50/60Hz + 115V 60Hz
- CFC-free refrigerant and insulation
- Compressor made for use in the tropics
- Solid lid with handle and lock
- Zinc coated evaporator tubing
- 3 baskets for organized storage

Specifications for MF 314		Dimensions for MF 314	
Gross volume, litres(cu. ft.)	281 (9.9)	Height, mm (inches)	840 (33.1)
Net volume, litres (cu. ft.)	271 (9.6)	Width, mm (inches)	1560 (61.4)
Temperature range, C°	-18 to -28	Depth, mm (inches)	700 (27.6)
Hold-over time during power cut at 43°C AMB, hrs	4	Gross weight, kg (lbs)	108 (238)
Power consumption per 24h, kWh	4.23	Net weight, kg (lbs)	87 (193)
Refrigerant	R134a		
No. of baskets	3		
Icepack freezing capacity, per 24 hrs.	7.2 kg		